



# CITY OF SPRING VALLEY VILLAGE



1025 CAMPBELL ROAD  
HOUSTON, TEXAS 77055

Phone 713-465-8308 or Fax 713-461-7969  
BACKFLOW PREVENTION ASSEMBLY  
CERTIFIED TEST REPORT  
TEST AND MAINTENANCE REPORT\*

ILLEGIBLE OR INCOMPLETE REPORTS WILL NOT BE ACCEPTED

Name of Property Owner: \_\_\_\_\_

Property Address: \_\_\_\_\_

City: \_\_\_\_\_ Zip: \_\_\_\_\_ Key Map # \_\_\_\_\_ Phone # \_\_\_\_\_

Mailing Address \_\_\_\_\_ Contact Person \_\_\_\_\_

THE BACKFLOW PREVENTION ASSEMBLY DETAILED HEREON HAS BEEN TESTED AND MAINTAINED AS REQUIRED BY TCEQ-CHAPTER 290, RULES AND REGULATIONS FOR PUBLIC WATER SYSTEMS, SPRING VALLEY STANDARD PLUMBING CODE, AND IS CERTIFIED TO COMPLY WITH THE REQUIRMENTS.

### TYPE OF ASSEMBLY

- REDUCED PRESSURE PRINCIPLE (RP)
- PRESSURE VACUUM BREAKER (PVB)
- DOUBLE CHECK VALVE (DCV)

- REDUCED PRESSURE PRINCIPLE-DETECTOR (RPD)
- SPILL-RESISTANT PRESSURE VACUUM BREAKER (SVB)

MANUFACTURER \_\_\_\_\_

MODEL # \_\_\_\_\_

SIZE: \_\_\_\_\_

SERIAL NUMBER \_\_\_\_\_

LOCATED AT \_\_\_\_\_

DATE INSTALLED \_\_\_\_\_

REDUCED PRESSURE PRINCIPLE ASSEMBLY			PRESSURE VACUUM BREAKER & SVB		
	DOUBLE CHECK VALVE ASSEMBLY		RELIEF VALVE	AIR INLET	CHECK VALVE
	CHECK VALVE #1	CHECK VALVE #2			
INITIAL TEST	D.C. CLOSED TIGHT ___ RP _____ PSI LEAKED _____	CLOSED TIGHT ___ _____ PSI LEAKED _____	OPENED AT _____ PSI DID NOT OPEN ___	OPENED AT _____ PSI DID NOT OPEN ___	HELD AT _____ PSI LEAKED _____
REPAIRS** AND MATERIAL USED					
FINAL TEST	D.C. CLOSED TIGHT ___ RP _____ PSI	CLOSED TIGHT ___ _____ PSI	OPENED AT _____ PSI	OPENED AT _____ PSI	HELD AT _____ PSI

TEST GAUGE USED: MAKE/MODEL: \_\_\_\_\_ S/N: \_\_\_\_\_ CALIBRATION DATE \_\_\_\_\_ (Tested Annually)

Remarks: \_\_\_\_\_

THE ABOVE TEST IS CERTIFIED TO BE TRUE, (The test results reflect the soundness of the assembly at testing time only.)

BACKFLOW TEST STATUS \_\_\_ PASS \_\_\_ FAIL

CT'S FIRM NAME: \_\_\_\_\_ CERTIFIED TESTER: \_\_\_\_\_

FIRM ADDRESS: \_\_\_\_\_ CERTIFIED TESTER NO. \_\_\_\_\_

FIRM PHONE # \_\_\_\_\_ TEST DATE: \_\_\_\_\_

\* TEST REPORTS MUST BE KEPT FOR AT LEAST THREE YEARS.  
TESTING IS REQUIRED FOR ALL BACKFLOW PREVENTION ASSEMBLIES UPON INSTALLATION (NEW, AND/OR REPLACEMENT.)  
\*\* USE ONLY MANUFACTURER'S REPLACEMENT PARTS